



Metal Mounting Enclosure IP66

A
021

A021 Metal Mounting Enclosure



Product Process:
Color : RAL7032
Production degree: IP66
Against mechanical impacts:IK10



Model	HxWxE(mm)	Thickness A class body/plate/door	Thickness B class body/plate/door	Thickness C class body/plate/door
MST253015-S	250x300x150	0.8/1.0/1.0	0.8/0.8/0.8	0.7/0.7/0.7
MST304015-S	300x400x150	0.8/1.0/1.0	0.8/0.8/0.8	0.7/0.7/0.7
MST405015-S	400x500x150	1.0/1.2/1.2	0.8/0.8/0.8	0.7/0.8/0.8
MST506015-S	500x600x150	1.0/1.2/1.2	0.8/0.8/1.0	0.8/0.8/0.8
MST304020-S	300x400x200	0.8/1.0/1.0	0.8/0.8/0.8	0.7/0.7/0.7
MST405020-S	400x500x200	1.0/1.2/1.2	0.8/1.0/1.0	0.8/0.8/0.8
MST406020-S	400x600x200	1.0/1.2/1.2	0.8/1.0/1.0	0.8/0.8/0.8
MST506020-S	500x600x200	1.0/1.2/1.2	0.8/1.0/1.0	0.8/0.8/0.8
MST507020-S	500x700x200	1.0/1.2/1.2	1.0/1.0/1.2	0.8/0.8/0.8
MST608020-S	600x800x200	1.2/1.5/1.5	1.0/1.2/1.2	1.0/1.0/1.0
MST8010020-S	800x1000x200	1.2/1.5/1.5	1.0/1.2/1.2	1.0/1.0/1.0
MST506025-S	500x600x250	1.0/1.2/1.2	1.0/1.0/1.2	0.8/0.8/0.8
MST608025-S	600x800x250	1.2/1.5/1.5	1.0/1.2/1.2	1.0/1.0/1.0
MST8010025-S	800x1000x250	1.2/1.5/1.5	1.0/1.2/1.2	1.0/1.0/1.0
Difference		A: Sealing by machine, Steel square lock	B: Sealing by machine, plastic round lock	C: Sealing by handmade, plastic round lock

Details of the enclosure:
CNC automatic production line

