



Insulated Female Disconnectors



ITEM NO	Name Tab(mm)	Material Thickness	Dimension(mm)					Color	Specification
			B	D	d	L	H		
FDD 1.25-110(5)	0.5x2.8	0.3	3.8	3.8	1.7	19.0	● Red	Terminal material: red copper conductor section: 0.5-1.5 mm ² (A.W.G: 22-16) Max Current: I max = 19A	
FDD 1.25-110(8)	0.8x2.8	0.3	3.8	3.8	1.7	19.0			
FDD 1.25-187(5)	0.5x4.75	0.35	5.6	3.8	1.7	19.0			
FDD 1.25-187(8)	0.8x4.75	0.35	5.6	3.8	1.7	19.0			
FDD 1.25-205	0.5x5.2	0.35	6.5	3.8	1.7	20.0			
FDD 1.25-250	0.8x6.35	0.4	7.4	3.8	1.7	21.0			
FDD 2-110(5)	0.5x2.8	0.3	3.8	4.3	2.3	19.0	● Blue	Terminal material: red copper conductor section: 1.5-2.5 mm ² (A.W.G: 16-14) Max Current: I max = 15A	
FDD 2-110(8)	0.8x2.8	0.3	3.8	4.3	2.3	19.0			
FDD 2-187(5)	0.5x4.75	0.35	5.6	4.3	2.3	19.0			
FDD 2-187(8)	0.8x4.75	0.35	5.6	4.3	2.3	19.0			
FDD 2-205	0.5x5.2	0.35	6.5	4.3	2.3	20.0			
FDD 2-250	0.8x6.35	0.4	7.4	4.3	2.3	21.0			
FDD 2-312	0.8x8.0	0.4	9.0	4.3	2.3	23.0			
FDD 5.5-187	0.5x4.75	0.4	5.6	3.4	5.7	23.0	● Yellow	Terminal material: red copper conductor section: 4-6 mm ² (A.W.G: 12-10) Max Current: I max = 25A	
FDD 5.5-250	0.8x6.35	0.4	7.4	3.4	5.7	25.0			
FDD 5.5-312	0.8x8.0	0.5	9.0	3.4	5.7	27			
FDD 5.5-375	1.2x9.4	0.5	10.9	3.4	5.7	29.6			

Fully Vinyl Insulated Disconnects



ITEM NO	Name Tab(mm)	material thickness	Dimension(mm)					Color	Specification
			B	d	D	L	H		
MDD 1.25-110(5)	0.5x2.8	0.5	2.8	1.7	4.3	17.7	10	● red	terminal head material: brass insulating material: Nylon I _{max} =10A
MDD 1.25-110(8)	0.8x2.8	0.8	2.8	1.7	4.3	17.7	10		
MDD 1.25-187(5)	0.5x4.75	0.5	4.75	1.7	4.3	20	10		
MDD 1.25-187(8)	0.8x4.75	0.8	4.75	1.7	4.3	20	10		
MDD 1.25-250	0.8x6.35	0.4x2	6.35	1.7	4.3	21	10		
MDD 2-110(5)	0.5x2.8	0.5	2.8	2.3	4.3	17.7	10	● blue	terminal head material: brass insulating material: Nylon I _{max} =15A
MDD 2-110(8)	0.8x2.8	0.8	2.8	2.3	4.3	17.7	10		
MDD 2-187(5)	0.5x4.75	0.5	4.75	2.3	4.3	20	10		
MDD 2-187(8)	0.8x4.75	0.8	4.75	2.3	4.3	20	10		
MDD 2-250	0.8x6.35	0.4x2	6.35	2.3	4.3	21	10		
MDD 5.5-187	0.5x4.75	0.5	4.75	3.4	5.7	23	13	● yellow	terminal head material: brass insulating material: Nylon I _{max} =24A
MDD 5.5-250	0.8x6.35	0.4x2	6.35	3.4	5.7	25	13		