

1kV Insulation Piercing Connector



CROP CHINA

Equivalent Type	CN Domestic code	Metric (mm ²)		A.W.G		Normal Current(A)	Dimensions mm	Weight (g)	Piercing Depth(mm)	Bolt Number
		Main	Service	Principal	Diversion					
PCT13C 6/6	CRS756	0.75-6	0.75-6	#20 - #10	#20 - #10	41	21x27x23	10	1-1.5	1
PCT13C 25/10	CRS101	1.5-25	1.5-10	#16 - #4	#16 - #8	44	27x41x62	55	1.5-2	1
PCT13C 120/10	CRSEP	6-120	1.5-10	#10 - #4/0	#16 - #8	55	27x41x62	55	1-2	1
PCT13C 50/25	CRS102	6-50	4-25	#10 - #1/0	#25 - #4	157	42x45x62	110	2.5-3.5	1
PCT13C 95/50	CRS2-95	6-95	4-50	#10 - #3/0	#25 - #1/0	157	46x52x87	160	2.5-3.5	1
PCT13C 120/35	CRS2-120	10-120	6-35	#8 - #4/0	#10 - #2	157	46x52x87	162	2.5-3.5	1
PCT13C 150/50	CRS2-150	50-150	6-50	#1/0 - #250 #300MCM	#10 - #1/0	157	46x52x87	162	2.5-3.5	1
PCT13C 95/95	CRS3-95	25-95	25-95	#4 - #3/0	#4 - #3/0	214	50x61x100	198	3-4	1
PCT13C 120/120	CRS3-120	16-120	16-120	#6 - #4/0	#6 - #4/0	214	50x61x100	198	3-4	1
PCT13C 150/150	CRS4-150	35-150	35-150	#2 - #250 #300MCM	#2 - #250 #300MCM	316	50x61x00	280	3-4	1
PCT13C 240/120	CRS6	120-240	25-120	#4/0 - #400MCM	#4 - #4/0	276	52x68x100	360	3-4	1
PCT13C 240/25	CRS7	150-240	10-25	#250MCM - #400MCM #300MCM	#8 - #4	102	52x68x100	336	3-4	1
PCT23C 150/150		16-150	16-150	#6 - #250 #300MCM	#6 - #250 #300MCM	316	70x65x90	360	3-4	2
PCT23C 240/240	CRS240	50-240	50-240	#4 - #400MCM	#4 - #400MCM	425	83x130x130	1020	4.5-5.5	2

* Special type can be required.