

B315 Anchoring clamp 4AN50.120(B)

PRODUCT DESCRIPTION:

xANa.b(B)S

x: core of conductor, AN: anchor clamp, a: min section of conductor, b: max section of conductor

B: small branch S:strip type

Anchoring clamps and their range are designed to cover most common overhead cable sizes. The body of a clamp is made from glass fiber reinforced polyamid and on the outer side are installed steel sheets only or steel sheets and stainless wire for better flexibility and making it easy to install the clamp to any kind of anchoring point.

PRODUCT RANGE:

- 4AN16.50S ◦ 4x 16 - 50 mm², 15 kN;
- 4AN16.120S ◦ 4x 16 -120 mm²,32 kN;
- 4AN16.120BS ◦ 4x 16 -120 mm²+ 2x 10 -35 mm², 32 kN

MATERIALS:

Anti-UV polyamid with fbg, H.D.G. steel, stainless steel.

PACKING:	4AN16.50	4AN16.120	4AN16.120B
Carton DIM (cm):	34x32x25	45x35x18	51x35x18
Contents (pcs):	40	25	25
Weight:	0.75 kg	1.055 kg	1.183 kg
Net weight:	30 kg	24 kg	26 kg
Gross weight:	31 kg	25 kg	27 kg

STORAGE AND TRANSPORT:

Product does not have any specific storage requirements. It is fire resistant and non-hazardous.

